




## Adhered Veneers & Wall Mounted Accessories

 is designed to meet or exceed building code requirements. Independent testing in accordance with ASTM C1670, Standard Specification for Adhered Manufactured Stone Masonry Veneer Units

*Supporting test data is available upon request.*

Local building codes may vary by area. Always check with your local building authorities before installing stone.

*For additional technical information please visit: [www.eldoradostone.com](http://www.eldoradostone.com)*

### Ingredients

Light weight aggregate ASTM C33, C330 & C331

Portland cement ASTM C150, ACI 318

Mineral oxide pigments ASTM C979

### Code Acceptability & Certification

UL Registered

Mineral composition units

Surface burning characteristics

Flame Spread 0

Smoke Developed 0

ICC-ES ESR-1215

California Building Code

Florida Building Code

### Absorption

Tested in accordance with ASTM C1670  
ICC-ES Acceptance Criteria 51 & ASTM C140

### Saturated Density - Weight per Square Foot

Tested in accordance with ASTM C1670 Weight less than 15 lbs per sq. ft., saturated

### Thermal Resistance

Tested in accordance with ASTM C177  
R value: 0.62 (ft<sup>2</sup>-F-hr)/BTU at 1.5" thickness

### Compressive Strength

Testing in accordance with ASTM C1670  
Compressive strength is greater than 2100 psi

### Wind Load Testing

Tested in accordance with ASTM E330 at  
150 mph wind speed, passed